

STANDARD DESIGN CONSTRUCTION									CUSTOMER SPECIFICATION DESIGN
Class 150			Class 300			Class 600			
DN	Wtk	Length	DN	Wtk	Length	DN	Wtk	Length	
2	3.9	350	2	3.9	350	2	3.9	350	
3	4.8	350	3	5.5	350	3	5.5	350	
4	4.8	350	4	6.0	400	4	6.0	400	
6	5.6	400	6	7.1	500	6	7.1	500	
8	6.4	400	8	8.2	500	8	8.2	500	
10	6.4	400	10	9.3	600	10	9.3	600	
12	6.4	450	12	10.3	600	12	10.3	600	
14	7.9	450	14	12.7	600	14	12.7	600	
16	9.5	500	16	12.7	700	16	12.7	700	
18	9.5	500	18	12.7	700	18	12.7	700	
20	9.5	600	20	12.7	800	20	12.7	800	
24	12.7	600	24	14.3	800	24	14.3	800	
30	12.7	800	30	15.9	1000	30	15.9	1000	
36	14.3	900	36	19.1	1100	36	19.1	1100	
48	15.9	1000	48	20.6	1200	48	20.6	1200	

- Size
- Materials
- Wall Thickness
- Fluid
- Type of installation
- Design Pressure
- Design Temperature
- Corrosion Allowance
- Dielectric Resistance
- Electric Insulation
- Design Loads
- Design Life
- Testing
- Coating